

Printing and Handling

- Suitable for use on Solvent, Eco Solvent, Latex and U.V. inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- Not recommended for edge to edge printing (10mm unprinted boarder)

Application

- Allow the inks to cure before application, minimum 36-48 hours.
- Apply to flat surfaces. Apply unstressed.
- Suitable for dry application only.
- Not recommended for use on low energy surfaces such as PP and PE. The user should determine suitability of substrate.
- For application to emulsion painted walls please refer to the DécorMark application Guide.

Face Film

Face Film:	Calendered PVC
Gauge:	100 micron nominal

Adhesive

Type	Dotted permanent clear acrylic.
Perceived tack	Medium
Application temperature	+10°C
Service temperature	-30°C to +120°C

Release Liner

Print	Plain
Weight	135 gsm nominal
Type	Kraft

Finishes

Finishes Available	MD-DOT-01	White Matt
	MD-DOT-02	Clear Matt

Roll Presentation

Roll sizes and net weights	1370mm x 50m	20kg
Presentation	Face film outwards, on a 76mm core.	

Durability

Shelf Life	1 year
External weathering	Indoor use.
Fire Rating	Self Extinguishing.
Dimensional Stability	<2% (48h at 70°C on aluminium)
Regulations	REACH compliant